

**MATERIAL SAFETY
DATA SHEET**

Peace Modern Town C-2408, Dalian, 116023, China
Tel: +86-411-84377919 Fax: +86-411-84511565
Web: www.sibond.com E-mail: info@sibond.com

NAME USED ON LABEL: **PROPYLTRIMETHOXYSILANE**
CHEMICAL NAME: PROPYLTRIMETHOXYSILANE
SYNONYMS: TRIMETHOXYPROPYLSILANE
CHEMICAL FAMILY: ORGANOSILANE ESTER
FORMULA: C₆H₁₆O₃Si
HMIS CODES HEALTH: 3 FLAMMABILITY: 3 REACTIVITY: 1

INGREDIENTS

IDENTITY	CAS NO.	%	TLV OSHA PEL
PROPYLTRIMETHOXYSILANE	1067-25-0	>95	not established
METHANOL 67-56-1	<2 skin, TWA: 200ppm		

PHYSICAL DATA

Boiling Point: 142°C	Melting Point: <0°C
Specific Gravity: 0.93	Vapor Pressure, 25°C: not determined
Vapor Density, air = 1: > 1	Solubility in water: insoluble, reacts slowly
% volatiles: 100	Evaporation rate (Butyl Acetate = 1): <1
Molecular Weight: 164.27	Other: NA
Appearance & Color: Clear liquid, characteristic odor	

FIRE & EXPLOSION DATA

Flash Point, TCC: 34°C (93°F) Autoignition Temp.: not determined
Flammability Limits: not determined
Extinguishing Media: Water spray or fog, foam, carbon dioxide, dry chemical.
Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe fumes or inhale vapors.
Unusual Fire and Explosion Hazards: Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

ENVIRONMENTAL INFORMATION

Spill response: Sweep material and transfer to a suitable container for disposal.
Recommended Disposal: Incinerate. Follow all chemical pollution control regulations.

HEALTH HAZARD DATA

On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system.
Eye Contact: Will cause immediate or delayed severe eye irritation.
Skin contact: May produce irritation or contact dermatitis which may be delayed several hours.

- 1-

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemical Abstract Service Registration Number
Sibond © 2010

Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects.
Inhalation: Inhalation of vapors or particulates of may irritate the respiratory tract. Overexposure may produce coughing, headache and nausea. |
Oral Toxicity - rat, LD50: 7240mg/kg

Chronic Toxicity: There are no known chronic effects related to this compound.
SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention, preferably from an ophthalmologist.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. Get medical attention.

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

REACTIVITY DATA

Stability: Stable

Conditions to avoid: Material decomposes slowly in contact with moist air or with water liberating methanol. Avoid contact with oxidizing agents..

Hazardous decomposition products: Ethanol, organic acid vapors and silicon dioxide.

SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV, NIOSH approved organic vapor respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

OTHER PRECAUTIONS

For research and industrial use only.

Storage and Handling: Store in sealed containers.

Containers require grounding during use.

TRANSPORTATION

DOT SHIPPING NAME: FLAMMABLE LIQUID, N.O.S.
(PROPYLTRIMETHOXYSILANE)

DOT HAZARD CLASS: 3

DOT LABEL: FLAMMABLE LIQUID

DOT ID No: UN1993 PG III

- 2 -

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemical Abstract Service Registration Number
Sibond © 2010

The information contained in this document has been gathered from reference materials and/or Sibond test data and is to the best knowledge and belief of Sibond accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Sibond makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore.

- 3-

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemical Abstract Service Registration Number
Sibond © 2010