

# MATERIAL SAFETY DATA SHEET

 Peace Modern Town C-2408, Dalian, 116023, China

 Tel: +86-411-84377919
 Fax: +86-411-84511565

 Web: www.sibond.com
 E-mail: info@sibond.com

NAME USED ON LABEL: 3-CHLOROPROPYLTRIMETHOXYSILANE CHEMICAL NAME: 3-CHLOROPROPYLTRIMETHOXYSILANE SYNONYMS: 1-CHLORO-3-(TRIMETHOXYSILYL)PROPANE CHEMICAL FAMILY: ORGANOSILANE FORMULA: C6H15CIO3Si HMIS CODES HEALTH: 3 FLAMMABILITY: 2 REACTIVITY: 1

### INGREDIENTS

IDENTITYCAS NO.%TLV3-CHLOROPROPYLTRIMETHOXYSILANE2530-87-2>95 not established(TLV for methanol: 200ppm - skin)

### PHYSICAL DATA

Boiling Point: 195-6°CFreezing Point: <0°C</th>Specific Gravity: 1.08Vapor Pressure, 100°: 40mmVapor Density (air=1): 6.9Solubility in water: reacts% volatiles: NAEvaporation rate: NAMolecular Weight: 198.72Other: NAAppearance & Color: Clear to straw liquid with mild odor.

## FIRE & EXPLOSION DATA

Flash Point, COC: 84°C (183°F) Autoignition Temp.: not determined Flammability Limits: not determined

Extinguishing Media: Water spray, foam, carbon dioxide, dry chemical. Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe fumes or inhale vapors.

Unusual Fire and Explosion Hazards: Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

#### **ENVIRONMENTAL INFORMATION**

Spill response: May be hazardous to aquatic life if released to open waters. Cover spill with absorbent material. Transfer to a suitable container for disposal. Recommended Disposal: Hydrolyze material by mixing with water in a hood. Organic layer may be incinerated. Alternately, absorb onto clay or vermiculite and dispose of absorbent material as solid waste. Follow all chemical pollution control regulations.

#### HEALTH HAZARD DATA

Eye Contact: Vapors may cause immediate or delayed severe eye irritation.

- 1-

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemical Abstract Service Registration Number Sibond © 2010

Liquid can cause severe conjunctivitis and corneal damage

Skin contact: May produce irritation or contact dermatitis which may be delayed several hours. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects.

Inhalation: A recent study indicated that chloropropyltrimethoxysilane is a genetically active material via inhalation in a bone marrow micronucleus assay in female rats exposed to 200ppm daily over a 28 day period. However, using the same assay, no evidence of genetic activity was found in mice exposed to 500, 1000, or 1625 mg/kg by intraperitoneal injection. The relevance of this information to humans has not yet been determined. Inhalation of vapors or particulates of will irritate the respiratory tract. Overexposure may produce coughing, headache and nausea.

Oral Toxicity: Not determined.

#### SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Call a physician. INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. Get medical attention.

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

## **REACTIVITY DATA**

Stability: Stable in sealed containers stored under dry nitrogen.

Conditions to avoid: Combustible; avoid contact with heat, sparks or open flame. Incompatibility (materials to avoid): Reacts with water and moisture in air liberating methanol. Avoid contact with peroxides, oxidizing agents, alcohols, acids, Lewis acids.

Hazardous decomposition products: Organic acid vapors, methanol.

#### SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended. Respiratory Protection: If exposure exceeds TLV air-supplied or combination organic vapor amine gas respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

- 2-

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemical Abstract Service Registration Number Sibond © 2010

#### **OTHER PRECAUTIONS**

For research and industrial use only. Storage and Handling: Store in sealed containers. Containers require grounding during use.

#### TRANSPORTATION

DOT SHIPPING NAME: COMBUSTIBLE LIQUID, N.O.S. DOT HAZARD: Not regulated DOT LABELS:Not Regulated DOT ID No: Not Regulated

The information contained in this document has been gathered from reference materials and/or Sibond test data and is to the best knowledge and belief of Sibond accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Sibond makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore.

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemical Abstract Service Registration Number Sibond © 2010