



a Supplier of Silicones from China

MATERIAL SAFETY DATA SHEET

Peace Modern Town C-2408, Dalian, 116023, China
Tel: +86-411-84377919 Fax: +86-411-84511565
Web: www.sibond.com E-mail: info@sibond.com

CHEMICAL NAME: 3-AMINOPROPYLTRIETHOXYSILANE

SYNONYMS: 3-(TRIETHOXYSILYL)PROPYLAMINE

CHEMICAL FAMILY: ORGANOSILANE

FORMULA: C₉H₂₃NO₃Si

HMIS CODES HEALTH: 3 FLAMMABILITY: 1 REACTIVITY: 1

INGREDIENTS

IDENTITY	CAS NO.	%	TLV	OSHA PEL
3-AMINOPROPYLTRIETHOXYSILANE	919-30-2	>97	not established	not established
ETHANOL	64-17-5	<1	1000ppm	1000ppm

PHYSICAL DATA

Boiling Point: 122-3°C at 30mm Freezing Point: <0°C
Specific Gravity: 0.951 @ 25°C Vapor Pressure, 100°: 10mm
Vapor Density (air=1): >1 Solubility in water: reacts
% volatiles: <40 Evaporation rate (butyl acetate =1): <1
Molecular Weight: 221.37 Other: NA
Appearance & Color: Clear to straw liquid with amine (ammonia-like) odor.

FIRE & EXPLOSION DATA

Flash Point, COC: 104°C (220°F) Autoignition Temp.: not determined
Flammability Limits- LEL: NA UEL: NA
Extinguishing Media: Water spray, foam, carbon dioxide, dry chemical.
Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe fumes or inhale vapors.
Unusual Fire and Explosion Hazards: Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

ENVIRONMENTAL INFORMATION

Spill response: May be hazardous to aquatic life if released to open waters. Cover spill with absorbent material. Transfer to a suitable container for disposal.
Recommended Disposal: May be incinerated. Alternately, absorb onto clay or vermiculite and dispose of absorbent material as solid waste. Follow all chemical pollution control regulations.

HEALTH HAZARD DATA

Eye Contact: Vapors may cause immediate or delayed severe eye irritation.
Liquid can cause severe conjunctivitis and corneal damage.
Skin contact: May produce irritation or contact dermatitis which may be delayed

- 1-

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemical Abstract Service Registration Number
Sibond © 2010

several hours. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects.

Primary irritation index: 6.50

Inhalation: Inhalation of vapors or particulates of aminoalkylsilanes will irritate the respiratory tract. Overexposure may produce coughing, headache and nausea.

Oral Toxicity - rat, LD50: 1780mg/kg.

Chronic Toxicity: There are no known chronic effects related to this compound.

SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. Get medical attention.

REACTIVITY DATA

Stability: Stable in sealed containers stored.

Conditions to avoid: Combustible; avoid contact with heat, sparks or open flame.

Incompatibility (materials to avoid): Reacts with water and moisture in air liberating ethanol.

Avoid contact with peroxides, oxidizing agents, alcohols, acids.

Hazardous decomposition products: Organic Acid Vapors.

SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV air-supplied or combination organic vapor amine gas respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

OTHER PRECAUTIONS

For research and industrial use only.

Storage and Handling: Store in sealed containers.

TRANSPORTATION

DOT SHIPPING NAME: CORROSIVE LIQUID, BASIC ORGANIC, N.O.S.
(3-AMINOPROPYLTRIETHOXYLANE)

DOT HAZARD: 8

DOT LABELS: CORROSIVE

DOT ID No: UN3267 PG: III

The information contained in this document has been gathered from reference materials and/or Sibond test data and is to the best knowledge and belief of Sibond accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Sibond makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore.

- 2 -

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemical Abstract Service Registration Number
Sibond © 2010

