

MATERIAL SAFETY DATA SHEET

Peace Modern Town C-2408, Dalian, 116023, China Tel: +86-411-84377919 Fax: +86-411-84511565 Web: www.sibond.com E-mail: info@sibond.com

NAME USED ON LABEL: DIPHENYLSILANEDIOL

CHEMICAL NAME: DIPHENYLSILANEDIOL SYNONYMS: DIPHENYLDIHYDROXYSILANE

CHEMICAL FAMILY: ORGANOSILANE

FORMULA: C₁₂H₁₂O₂Si

HMIS CODES HEALTH: 2 **REACTIVITY: 0** FLAMMABILITY: 2

INGREDIENTS

CAS NO. **TLV** % **IDENTITY** DIPHENYLSILANEDIOL 947-42-2 >90 not determined

(OSHA PEL, nuisance dust: 15mg/m₃)

PHYSICAL DATA

Boiling Point: not determined Melting Point: 138-142°C- decomposes Vapor Pressure at 25°C: not determined Specific Gravity: not determined

Vapor Density: NA Solubility in water: insoluble

% volatiles: NA Evaporation rate: NA

Other: N/A Molecular Weight: 216.32

Appearance & Color: White powder

FIRE & EXPLOSION DATA

Flash Point, COC: 53°C Autoignition Temp.: not determined

Flammability Limits: not determined

Extinguishing Media: Water spray, foam, carbon dioxide, dry chemical.

Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe

fumes or inhale vapors.

Unusual Fire and Explosion Hazards: Irritating fumes and organic acid vapors

may develop when material is exposed to water or open flame.

ENVIRONMENTAL INFORMATION

Spill response: May be hazardous to aquatic life if released to open waters.

Transfer to a suitable container for disposal.

Recommended Disposal: May be incinerated. Alternately, mix with clay or vermiculite and dispose of absorbent material as solid waste. Follow all chemical pollution control regulations.

HEALTH HAZARD DATA

Eye Contact: May cause immediate or delayed severe eye irritation.

Skin contact: May produce irritation or contact dermatitis which may be delayed

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemical Abstract Service Registration Number Sibond © 2010

several hours. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects.

Inhalation: Inhalation of vapors or particulates of may irritate the respiratory tract.

Overexposure may produce coughing, headache and nausea.

Oral Toxicity: Not determined.

Chronic Toxicity: There are no known chronic effects related to this compound.

TOXICITY- ipr mus, LD50: 2500mg/kg

SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or

having convulsions. Get medical attention.

REACTIVITY DATA

Stability: Stable in sealed containers stored under a dry inert atmosphere. Conditions to avoid: Combustible; avoid contact with heat, sparks or open flame. Incompatibility (materials to avoid): Avoid contact with alcohols, acids, oxidizers. Hazardous decomposition products: Organic acid vapors.

SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV air-supplied or combination

organic vapor/acid gas respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

OTHER PRECAUTIONS

For research and industrial use only.

Storage and Handling: Store in sealed containers.

TRANSPORTATION

DOT SHIPPING NAME: DIPHENYLSILANEDIOL, FLAMMABLE SOLID, N.O.S.

DOT HAZARD CLASS: 4.1

DOT LABEL: FLAMMABLE SOLID DOT ID No: UN1325 PG II

The information contained in this document has been gathered from reference materials and/or Sibond test data and is to the best knowledge and belief of Sibond accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Sibond makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore.